

Resene Silvalusta

Resene Silvalusta is a solventborne black bitumen cut to brushing viscosity with the addition of a leafing grade aluminium flake.

exterior

Typical uses

- Bitumen roofing
- Downpipes and flashings
- Galvanised iron (new and old)
- Roof gutters and channels
- Water pipes

Vehicle type	Bitumen
Pigmentation	Aluminium paste
Solvent	Hydrocarbon
Finish	Matt
Colour	Silver
Dry time (minimum)	1 hour
Recoat time (minimum)	24 hours
Primer required	No
Theoretical coverage	15 sq. metres per litre
Dry film thickness	23 microns at 15 sq. metres per litre
Usual no. of coats	2
Abrasion resistance	Poor
Chemical resistance	Poor – acids and alkalis
Heat resistance	Thermoplastic
Solvent resistance	Poor
Durability	Good
Thinning and clean up	Mineral turps
VOC	509 grams per litre

Physical properties

Performance

Performance

1. Excellent intercoat adhesion and to all surfaces.
2. Totally resistant to moss and mould growth.
3. Excellent reflective value.
4. Ideal on tar exteriors to reduce temperature.

Silvalusta

Surface preparation

Clean down thoroughly to remove all dirt, dust and loose material. Ensure surface is free from oil, grease, moss and mould.

If moss and mould are present, treat with Resene Moss & Mould Killer (see [Data Sheet D80](#)). Waterblasting at 21,000 kps (3000 psi) is the best surface preparation method prior to painting weathered or existing painted surfaces.

Application

Apply by brush, roller or spray. Many coats can be applied for maximum protection with no shrinking or cracking of the film.

Precautions

1. Resene Silvalusta develops maximum brilliance after six weeks weathering.
2. FLAMMABLE – Keep away from heat and open flame. Keep closed when not in use.
3. Avoid breathing vapour – use with adequate ventilation.

*Please ensure the current Data Sheet is consulted prior to specification or application of Resene products.
If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*

In Australia
PO Box 785, Ashmore City, Queensland 4214
Call 1800 738 383, visit www.resene.com.au
or email advice@resene.com.au

Resene
the paint the professionals use

In New Zealand
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Call 0800 RESENE (737 363), visit www.resene.co.nz
or email advice@resene.co.nz