

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

Resene

Aquaclear

waterborne urethane varnish
interior

The background of the lower half of the advertisement features three ducks in a pond. On the left is a brown duck, in the center is a yellow duck, and on the right is a grey duck. The water is depicted with orange and red ripples. The ducks are rendered in a stylized, almost wood-like or ceramic-like texture.

WARNING

KEEP OUT OF REACH OF CHILDREN



9 418022 024347

SATIN

LL240001F 4/24

net contents 1 litre

LL2400001B 4/24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONS

DO NOT BREATHE MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131
126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON
(764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D59.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth.

Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT:

Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Aquaclear has been developed as a waterborne alternative to turps thinned oil modified urethanes to enhance and protect timber. Where maximum abrasion resistance is required, such as high traffic floors, a moisture-cured urethane, such as Resene Polythane, is recommended.

Preparation

- Ensure surfaces to be coated are in sound condition, dry, free from dirt, dust, loose material, oil and grease.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Stop all nail holes and cracked timber with a suitable filler.
- Stand thoroughly varnished surfaces to remove all gloss and provide a key for good adhesion. Use Resene Interior Paintwork Cleaner to ensure the surface to be painted is clean and free from grease, paying particular attention to hand contact areas. Sand to de-gloss/profile using 220 grit sandpaper. If old varnish is flaking everything must be removed to ensure a uniform appearance.
- Sand and clean bare timber surfaces prior to coating. Finish off with fine sandpaper to achieve a smooth finish, remembering always to sand with the grain.
- This product may be applied direct over a painted surface finished in Resene FX Metallic or Resene pigmented topcoats for extra protection – no sanding needed.
- Thoroughly vacuum all surfaces to remove surface contaminants and sanding dusts. Pay special attention to residual floor polish in the gaps between tongue and groove flooring.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate-based paints or old asbestos containing building materials may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- This product may be used to coat a wide variety of surfaces. If the surface you propose to coat is unsure or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

Application

- For uncoated surfaces thin the first coat with up to 10% clean water.
- Stir thoroughly with a wide flat stirrer before and during use.
- Apply with a speed brush, synthetic bristle brush or Resene No.4 roller (product can be sprayed). Apply evenly. Avoid working over a surface that has begun to set as this will give a patchy appearance.
 - Do not brush or roll excessively as that can cause foaming.
 - Do not apply in direct sunlight.
 - Allow 72 hours to reach full cure. Use stockings feet on floor prior to full cure.
 - Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system when painting in marginal painting conditions. Do not use gas or diesel burners to heat the coated area as these produce water that will inhibit drying and curing. Poor ventilation may affect appearance and performance.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

Quick check

Use on: Interior timber surfaces.

Gloss level: Satin, semi-gloss and gloss. Resene Aquaclear Natural is also available in a flat finish for timber walls and ceilings.

Coverage (average): 12 square metres per litre per coat. Spreading rates are given for bare timber – take care not to overspread on sealed surfaces.

Dry time (minimum): 30 minutes. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 2 hours.

Primer required: No.

Usual number of coats: Three. New work – four minimum.

Application method: Speed brush or synthetic bristle brush for small areas. For flooring apply using a Resene No.4 roller sleeve. Contact Resene Technical Services for spray application recommendations.

Thinning and clean up: Water. First coat may be thinned with up to 10% clean water.

In hot and dry conditions: Application is difficult at high temperatures and low humidity. Up to 5% Resene Hot Weather Additive may be added.

Colour range: Turbid – dries clear.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Data Sheet and Safety Data Sheet before application.

Please ensure that use of this product is compatible with the substrate and surface preparation. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



Aquaclear SDS



Aquaclear TDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hunt 5045
Ph (04) 577 0500 Visit resene.co.nz