

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

Fresh Air

pollution eating paint

waterborne interior satin



KEEP OUT OF REACH OF CHILDREN



WHITE
DO NOT TINT

WARNING

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply.

FIRST AID

SWALLOWED: If significant amounts have been ingested give water to dilute. Do not cause vomiting. Get medical attention without delay.

SKIN: If significant skin contact occurs wash skin thoroughly with soap and water. Do not scrub skin.

EYES: Hold open and flood with water for at least 15 minutes. Get medical attention without delay.

When seeking medical advice take this container with you. Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D319.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Resene Fresh Air - Carparking is a semi-transparent waterborne satin topcoat with photocatalytic pigments. Designed to break down NOx and organic atmospheric pollutants that come into contact with the film. Apply as a thin topcoat over a white substrate. This product has been designed for use in interior carparks. Activity is increased with increasing light flux.

Preparation

- Ensure surfaces to be painted are in sound condition, dry and free from dirt, dust, loose material and salt. Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).

- Waterblasting is the best surface preparation prior to painting of weathered cementitious surfaces, galvanised steel and Zincalume.

- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry **must be treated** (see Data Sheet D83).

- Wherever oil and grease are present and when painting galvanised steel or Zincalume, ensure the surface to be painted is thoroughly cleaned using Resene Roof Wash and Paint Cleaner (see Data Sheet D88). Flush clean with water.

- Fill cracks and holes in timber after priming. Fill cracks and holes in interior walls before sealing.

- Round all sharp timber edges. Any bare timber surface that has been left exposed to the weather for more than one week must be thoroughly sanded or treated with Resene TimberLock (see Data Sheet D48).

- Ensure cementitious surfaces are fully cured, or treated with Resene Limelock (see Data Sheet D809), before coating. Undercured cementitious surfaces can significantly affect the performance and colourfastness of applied paint.

- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Application

- Prepare and prime with Resene Quick Dry primer (see Data Sheet D45). Apply one coat of Resene Fresh Air Carparking. A full white coat is required under Resene Fresh Air Carparking to ensure it functions effectively.

- Apply by brush, speed brush, synthetic fibre roller (Resene No.1) or spray. Do not thin.

- Spray application: Use an airless spray unit capable of delivering a flow rate of not less than 2 litres per minute such as Graco Ultra 395. A FT 410 tip is recommended with 60 mesh gun and filters. Apply to achieve an even wet film at a spreading rate of 14 square metres per litre with greater than 50% overlap.

- Maintain good ventilation throughout the drying and curing period to ensure the paint is properly cured. Poor ventilation may inhibit curing and performance.

- At the end of its serviceable life, wash down Resene Fresh Air Carparking with Resene Paint Prep and Housewash. Reapply Resene Quick Dry if required to provide a white basecoat, allow to dry and then apply Resene Fresh Air Carparking. If the white basecoat is still sound after the surface is washed and dried, Resene Fresh Air Carparking may be applied directly.

Maintenance

(after a minimum of four weeks' drying)

See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

Be Paintwise

For tips on minimising the impact of your decorating on the environment see the Resene website.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited

7 Production Ave, PO Box 785, Ashmore City, Queensland, 4214

Phone 1800 738 383 Fax 1800 064 960

Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited

Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045

Phone (04) 577 0500 Fax (04) 577 0600

Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper that complies with EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Interior carparking areas including brick, concrete and fibre cement.

Gloss level: Satin.

Coverage: 14 square metres per litre per coat

Dry time (minimum): 30 minutes at 18°C and less than 85% humidity. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat: Not recommended.

Basecoat required: Yes – white.

Usual number of coats: One

Application method: Apply by brush, speed brush, synthetic fibre roller (Resene No.1) or airless spray.

Thinning: Thinning not recommended, supplied at application viscosity.

Clean up: Water.

Colour range: Semi-transparent white, substrate colour will show through. Not suitable for tinting.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of Quality Guarantee on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.